



Architectural Specification

Nordock WEARTOUGH™ Series – Model DS Truck Dock Shelter

Section 11164

Dock Seals and Shelters

Part 1 - General

1.01- WORK INCLUDED

- A. Factory assembled unit with necessary mounting hardware.
- B. Installation and Owners Manual

1.02 - RELATED WORK

- A. Section 11161 – Dock Levelers.
- B. Section 11160 - Trailer Restraints.
- C. Section 11165 - Dock Bumpers.

1.03 – REFERENCES

- A. Government Test Method Standard No.191A for fabric.

1.04 - DESCRIPTION (APPLICATION)

- A. Door Size - Unit shall accommodate an opening size of _____" wide x _____" high.
- B. Dock Height - Loading dock height shall be _____".
- C. Bumper - Total dock bumper protection including any building wall offset or building wall overhang shall be _____".
- D. Drive Approach - Driveway shall have a _____ approach.
- E. Service Range - Unit shall be designed to service vehicles ranging in height from _____' - _____" to _____' - _____".

1.05 – SUBMITTALS

- A. Manufacturers Installation Instructions.
- B. Submit dimensional drawing.
- C. Submit specification sheet.

Part 2 - Products

2.01 - ACCEPTABLE MANUFACTURERS AND MODEL

- A. Model DS as manufactured by Nordock Inc.

2.02 - EQUIPMENT

- A. COMPONENTS: Each unit shall consist of (2) two side frames, side curtains, draft pads, steel protectors and (1) one head frame and head curtain.
- B. FRAMING: Stationary frames shall be constructed of superior grade kiln dried lumber covered with U. V. treated translucent rigid plastic securely fastened to framing. The head frame to be peaked for drainage. Provide steel guards to protect side frames.
- C. CURTAINS: Vertical curtains shall contain flexible fiberglass stays to keep the curtain straight and apply sealing pressure on trucks. Guide stripes provided to aid in spotting trailers. Head curtain shall include wear pleats on each side, full height flexible fiberglass stays and wind straps to hold panel in position. All fiberglass stays to be enclosed in reinforced pockets. Curtains shall be secured to frame with angle trim.
- D. PROJECTION: Unit projection shall be a minimum 14" beyond the face of the dock bumpers.
- E. FABRIC: The curtain fabric shall be _____.
- F. WARRANTY: Unit shall include the manufacturers standard a (1) one year warranty against defects in materials and workmanship.
- G. OPTIONS: To include the following options,

_____.

Part 3 - Execution

3.01 – INSTALLATION

- A. Install in accordance with manufacturer's instructions.
- B. Caulk between the building wall and unit.